

QUAD TRON, INC.

303 Camars Drive
Warminster, PA 18974

Phone: (215) 441-9303
Fax: (215) 441-9305
www.quadtron.com
Email: quadtron.inc@gmail.com

MICRO PCM ENCODER SERIES

MODEL MI_RTD_ADD12_4W

12 CHANNEL 4 WIRE RTD ADD ON MODULE

The MI_RTD_ADD12_4W add on RTD conditioning module stacks on top of the MI_RTD16_3W or the MI_RTD_ADD12_4W to add 12 additional 4 wire RTD channels. Multiple 3 wire or 4 wire add on modules may be stacked on top of a MI_RTD12_4W module. Add on modules provide reduced power consumption per channel with less weight.

The 12 channel RTD add on module, MI_RTD_ADD12_4W, is a very accurate 4 wire RTD conditioner with industry leading channel density, weight and low power.

Each of the 12 channels consists of:

- a 24 bit delta sigma A/D converter with built in low pass filtering for anti aliasing,
- a one pole low pass analog filter for anti aliasing,
- constant current source excitation,
- a precision reference resistor for ratiometric RTD measurement
- dynamic offset error removal and
- an FIR filter.

American ($\alpha = 0.00392 \Omega/\Omega/^\circ\text{C}$) and European ($\alpha = 0.00385 \Omega/\Omega/^\circ\text{C}$) ohms conversion for temperature output provided for most common RTD types. Resistance mode provides output resistance in ohms.

Both continuous constant current excitation and pulsed excitation modes selectable. Pulsed excitation mode reduces self heating.

Each channels FIR filter, is programmable for 1, 2, 4, 8, 16, 32, 64, 128, 256, 512, or 1024 taps providing improved noise reduction. Each channels sample rate is 370 Hz.

Two wire measurements supported.

Electrical Specifications:

TRANSDUCER TYPE: RTD's of 100 ohm, 200 ohm, 500 ohm, and 1Kohm

EXCITATION: Constant current, programmable per channel, 0.210, 0.4200, 1 or 2 milli amp.

ACCUARCY: ±0.25% of full scale accuracy

Environmental:

Operating Temperature: -40°C to +85°C
Storage Temperature: -55°C to +125°C
Humidity: Relative humidity of 85% for two hours at 65°C.
Altitude: Unlimited
Vibration: 20g's RMS from 5 to 2000Hz in each major axis.
Acceleration: Constant acceleration of 100g's in each axis.
Shock: 100g's for 10m second in each major axis.

Mechanical:

Size:

	inches	mm
Length	3.50	88.9
Width	1.25	31.75
Height	0.291	7.39

Weight: 25 g

Engraving: MI_RTD_ADD16_3W

J1 CONNECTOR : Nanonics # STMO51M6HN; TE Connectivity # 4-1589487-5

MATE: Nanonics # STMO51PC2DC018N; TE Connectivity # 7-158947-7

qtd.101136.15.03.10

QTI Quad Tron Inc.

Specifications subject to change without notice.